

CALACATTA

Technical Details

TINO NATURAL
STONE



CALACATTA

Natural Stone (Calcitic Marble) of creamy white color with subtle gray veins.

Its aesthetics and color tone make this stone an ideal product for interior design and applications in bathrooms, kitchens, countertops, showers, etc ...

Its enormous physical-mechanical performance adds to this stone an added value that allows designers to apply this product in any of their designs without fear of maintenance.

Calacatta has been the product chosen by the most distinguished Architects and Interior Designers in the field of Natural Stone floorings and Luxury Hospitality.

MECHANICAL PHYSICAL PROPERTIES

PROPERTY	STANDARD	VALUE
Water absorption	UNE EN 13755	0,10%
Flexural strength	UNE EN 12372	10,2 Mpa
Abrasion resistance	UNE EN 14157	26 mm
Frost Reistance	UNE EN 1341	Resistant
Bulk density	UNE EN 1936	2,72 g/cm ³
Compressive strength	UNE EN 1926	104,5 Mpa
Breaking load at dowel hole	UNE EN 13364	1300 N
Open porosity	UNE EN 1936	0,20%



SIZES

Sizes can be adapted to each project requirements. Standard thickness is 2cm and maximum size for this thickness is 240x140cm. For other thickness check available sizes.

Dimensional tolerance limits according to standards UNE-EN 12058 and UNE-EN 1341.

Standard surface finishes are:  **POLISHED**  **HONED**  **DOMUS**  **SANDBLASTED**

RECOMMENDED USES

	RESIDENTIAL	COMMERCIAL
Indoor Cladding	✓	✓
Outdoor Cladding	✓	✓
Indoor Flooring	✓	PLEASE CHECK
Outdoor Flooring	PLEASE CHECK	PLEASE CHECK
Countertops	PLEASE CHECK	PLEASE CHECK
Others	PLEASE CHECK	PLEASE CHECK

Tino Group has completed
more than 600 projects with
clients from around the world.

CONTACT US

www.tinostone.com

apina@tino.es

MARBELLA

(+34) 952 906 149

Ctra. Na. 340, Km 175 Río Verde
Puerto Banús 29660

MADRID

(+34) 917 811 857

Calle Padilla 30, 28006 Madrid

